

Sharp P721Q

Professional DLP 4K UHD Laser Projector

Datasheet



Sharp P721Q 4K UHD projector

Featuring crisp pixel-free 4K UHD image resolution and brightness of 7,200 ANSI lumen, the Sharp P721Q laser projector delivers exceptional image quality in perfect detail-rich clarity. Rooted in NEC's legacy of quality and projection expertise, the new Sharp-branded DLP projection family is redefining large surface visual experiences in meeting rooms, museums, and higher education establishments.

Requiring zero maintenance over a long 20,000-hour lifespan, the sealed optical engine and laser light source means filter and lamp replacement is obsolete. Professional installation capabilities achieve the finest image alignment through motorized zoom and focus, complemented by a fully motorized lens shift for precision and clarity. Highly versatile, it's easy to position the projector, simplifying installations and potentially reducing setup costs. With Risk Group 2 compliance, the new models eliminate the need for prescribed safety precautions, ensuring a safe and worry-free operating environment.

Benefits

Outstanding picture quality – a whole new visualization experience with up to 4K UHD pixel-free resolution for large surface detail-rich information

IP5X rated optical engine – protects against dust ingress for long lasting picture quality

Advanced Colour Sequence Management – eliminates the colour breaking phenomena

Professional and Flexible Installation - versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

No lamp replacement - up to 20,000 h maintenance free operation possible due to Laser Light Source.

Product Information

Product Name	Sharp P721Q
Product Group	Professional DLP 4K UHD Laser Projector
Order Code	60006067

Image

Projection Technology	1-chip DLP™ Technology
Panel Resolution	1920 x 1080 (FHD)
Resolution	3840 x 2160 (4K UHD)
Aspect Ratio	16:9
Contrast Ratio	3000000:1
Brightness	7200 Lumen (approx. 60% in Eco Mode); compliant with ISO21118-2020
Lamp	Laser Light Source
Light Source Life [hrs]	20000 ¹
Lens	F= 2-2.4, f= 18.72-29.59 mm
Lense Adjustment	Motorized
Lens shift	H:±25, V:+55,-55
Keystone correction	+/- 40° manual horizontal / +/- 40° manual vertical
Projection Factor	1.25 - 2 : 1
Projection Distance [m]	1.6 - 13.4
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 152 / 60"
Zoom	Motorized; x1.6
Focus Adjustment	Motorized
Supported Resolutions	3840 x 2160 (Maximum resolution of digital input)

Connectivity

Digital	Input: 1 x HDBaseT; 2 x HDMI™ supporting HDCP
Audio	Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	1 x Type B (for Service); 1x Type A (USB 2.0 high speed) with 1.5A Power Supply
Video Signals	NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Output:	1 x 3.5 mm Stereo Mini Jack for Screen Trigger
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select

Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	520 (Normal) / 280 (Eco) / 2 (Network Stand-by) / 0.5 (Stand-by)

Mechanical

Dimensions (W x H x D) [mm]	486 x 176 x 432.5 (without lens and feet)
Weight [kg]	14.7
Fan Noise [dB (A)]	34 / 36 (Eco / Normal)
Colour Versions	White

Environmental Conditions

Operating Temperature [°C]	0 to 45
Operating Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60
Storage Humidity [%]	20 to 80

Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved
Speakers [W]	2 x 10 (mono)

Additional Features

Special Characteristics	3D ready; AMX Beacon; Auto Power ON/OFF; Carbon Savings Meter; Constant Brightness Mode; Control ID Function; Crestron RoomView; DICOM simulation; Free Tilt; Geometric Correction; HDBaseT; Help Function; HTTP Browser Control; IP5X/IP6X rated; Kensington security slot; Keypad Lock; Lens Memory; Light Source Adjustment; Magnify; NaViSet Administrator 2; OSD with 21 languages; Password Security System; PJ LINK; Portrait Setting; Quick Start; Sealed engine; Source Select with Beep Function; Test Pattern; Unique Power Saving Functions; USB Viewer
-------------------------	---

Green Features

Ecological Materials	Downloadable manuals; ECO packaging
Ecological Standards	ErP compliant; RoHs compliant

Warranty

Projectors	3 years pan-European service
Light Source	3 years or 10000h (whatever comes first)

Shipping Content

Shipping Contents	2x AAA Batteries; IR Remote Control (RRMCG0002VW01); Power Cord (3 m); Projector; Quick Setup Guide; Security Sticker
-------------------	---

Optional Accessories

Optional Accessories	Universal Ceiling Mounts (PJ01UCM, PJ02UCMPF)
----------------------	---

¹ 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.

* This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.



CE



ErP



RoHS



TUEV Type Approved

This document is © 2024 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 16.12.2024